

GFCI

USER ATTACHABLE IN-LINE GFCI

Tower's User attachable in-line GFCI



30396029-08

Model 30396029-08 manual reset in-line GFCI can be added to or replace a GFCI plug on any power tool or equipment power cord.

A line side cord with molded plug is provided. User can wire load side cord. Hardware is provided to allow wiring to cord gauges 16/3, 14/3 and 12/3 SJTW.

The bright "Red" light indicates when the power is "ON". The TEST and RESET buttons allow for periodic testing.

FEATURES

MODEL 30396029-08

- Compatible with 15 amp U-ground outlets and plugs, 2 or 3 wire
- Trip level 4-6 mA
- UL and CUL listed
- Manual reset
- Rated for indoor and outdoor use

SPECIFICATIONS

- Class "A" people protection GFCI
- Rated for 125 volt, 15 amp use
- 1875 watts, 60 Hz
- LED Power "ON" indicator
- Open neutral and ground neutral protection
- Operating temperature range -35 degree C to 66 degree C
- Impact resistant case

SIMILAR MODELS

MODEL 30338023
USER ATTACHABLE
IN-LINE GFCI

MODEL 30396500-08
CORDLESS USER
ATTACHABLE IN-LINE
GFCI, 20 AMP